Ongoing DLR Research on Alternative Fuels and Aviation Emissions

Hans Schlager **DLR-Institute of Atmospheric Physics**

ACCESS-II Workshop Kissimmee, FL, USA 10 Jan. 2015





Europe's Vision for Environmentally Compatible Development of Aviation

EU Flightpath 2050:

Key Challenge: Protecting the environment & securing energy supply

ACARE Targets 2050:

Establishment of sustainable alternative fuels (share 2% in 2020, 25% in 2035, 40% in 2050)

EU Advanced Biofuels Flightpath Initiative

Promote production, distribution, storage, and use of biofuels

Goal: 2 million tons of biofuel are used in the EU by 2020 in the aviation sector



Ongoing DLR Projects

ECLIF (2014-2018):

Emissions and Climate Impact of Alternative Fuel

WeCare (2013-2017):


Mitigation of non-CO₂ climate effects of aviation, incl. studies of cirrus clouds originating from contrails and soot

Future Fuels (2015-2017):

Alternative liquid energy for electrical power production and global transport



ECLIF: Emissions and Climate Impact of Alternative Fuel Coordination: Patrick Le Clercq





Fuel Properties


Thermo-physical and thermo-chemical characterization of fuels —
Jet A-1 > Drop-in alt. fuels > Near-Drop-in alt. fuels

Experiments:


- Characterization of fuel composition
- Measurement of characteristic fuel properties (Distillation curve, Smoke Point, Density, etc.)
- Measurement of ignition-delay time and flame speed

Model development:

- Comprehensive reaction models based on these experimental data
- Modeling of thermo-physical and thermo-chemical properties









Laboratory Measurements

Detailed measurements of fuel effects on combustion behavior and emissions
Use of an optically accessible generic gas turbine combustor

Characteristics

- Fuel mass flow 2 5 kg/hour
- Air volume flow 400 800 l/min
- Air pre-heat up to 473K
- Pre-filmer airblast atomizer

Diagnostics


- PIV (innert)
- OH-LIF and formaldehyde-LIF
- Spray Characteristics (PDA, SLIPI)
- Chemiluminescence
- LII & emissions at outlet (probe)





Rig Testing

- RQL medium including cruise pressure multisector with optical access is operated in cooperation with Rolls-Royce Germany
- Comparison of soot concentration in the combustor (production) with concentration and number at exit (oxidation).



- Laser induced incandescence (LII) within the combustor smokemeter & SMPS at combustor exit.
- Results incorporated in emissions modeling



Emission Modeling

Numerical analysis and prediction of fuel effects on combustion


behavior and emissions


Detailed simulation of combustion chamber processes including emissions

Model with multi-species reaction mechanism

 Implementation of reduced mechanisms for target alternative fuels

 Transfer of detailed findings for lab-scale combustion chambers to large-scale combustion systems







Atmospheric Measurements

Comprehensive flight tests:

- Primary emissions and initial contrails (near field, plume age 0.5-2 s)
- Aged contrails (far field, plume age 1-5 min)

Ground tests: after each flight

Fuels: 5 different FT fuels + HEFA

Campaigns: 2015, 2016

Base: previous DLR campaigns and

ACCESS-II






Engine Performance, Flight Mission and Global Emissons Simulations

 Alternative fuel engine performance predictions


- Prediction of emissions at different flight altitudes and operating conditions (adaption of correlation methods)
 - Calculations of global emissions






Process Studies and Global Modeling of Contrails and their Climate Impact

 Plume processing and contrail formation



 Global modeling of contrail cirrus and their radiative effect



Radiative forcing due to air traffic



ECLIF-I Measurement Campaign 14 Sept. 2015 – 02 Oct. 2015, Germany

ECLIF-II Measurement CampaignAutumn 2016, Germany

Cooperation:

DLR-Institute of Atmospheric Physics DLR-Institute of Combustion Technique DLR-Institute of Propulsion Technique NASA Langley Research Center NRC Canada IFAR - Partners

